

DNA Line Inductor Specification Sheet ^{R2}

Dissipative Noise Attenuation
Model IND100

DNA Line Inductor
Model: IND100 Single

- Size: 12 in x 12 in x 8 in
- Lift - Off cover
- Environmental Rating: NEMA 1
- Material: Powder Coated Steel
- Color: Gray
- Knockouts: 20
- Mounting Holes: 4
- Empty Enclosure Certifications:
UL Listed and CSA Certified



- Maximum (Max) Line Voltage: 250 VAC, RMS, 50/60 Hz.
- Nameplate Max Current all IND100 models: 100 amperes AC, RMS, 50/60 Hz.
- For Filtering Performance, Max Current all IND100 models: 105 amperes AC, RMS, 50/60 Hz.
- For Safety/Overload Max Current all IND100 models: 150 amperes AC, RMS, 50/60 Hz.
- Max wire gauge on internal terminal strip IND100: 2/0 AWG to 6 AWG
- Current Capacity of Internal Wiring: 181 amps RMS
- Current Capacity of Terminal Strip: 150 amps RMS
- **Enclosure and All components inside enclosure are UL Listed.**

Noble Electronics, Inc.
1973 155th St. Fairfield, IA 52556, <http://mxdna.com/>
We have 23 Dealers throughout the US. Visit our website to find a Dealer close to you.