

DNA Line Inductor Specification Sheet ^{R3}

Dissipative Noise Attenuation

DNA Line Inductor

- Model: IND100 Single
- Size: 12 in. x 12 in. x 6 in.
- Lift-Off Cover
- Environmental Rating: NEMA 1
- Color: Grey
- Knockouts: 20
- Mounting Holes: 4
- Empty Chassis Certifications:
UL Listed and CSA Certified



- Maximum (Max) Line Voltage: 250 VAC, RMS, 50/60 Hz.
- Nameplate Max Current all IND100 models: 100 amperes AC, RMS, 50/60 Hz.
- For Filtering Performance, Max Current all IND100 models: 105 amperes AC, RMS, 50/60 Hz.
- For Safety/Overload Max Current all IND100 models: 150 amperes AC, RMS, 50/60 Hz.
- Max wire gauge on internal terminal strip IND100: 2/0 AWG to 6 AWG
- Current Capacity of Internal Wiring: 181 amps RMS
- Current Capacity of Terminal Strip: 150 amps RMS
- Weight: 45 lbs.
- Note: There are various loads that can cause the IND to audibly buzz. This is normal operation.
- **Enclosure and All components inside enclosure are UL Listed.**

Noble Electronics, Inc.

1973 155th St. Fairfield, IA 52556, <http://mxdna.com/>

We have 23 Dealers throughout the US. Visit our website to find a Dealer close to you.