

DNA Line Inductor Specification Sheet ^{R3}

Dissipative Noise Attenuation

Model IND30

Enclosure Data

DNA Line Inductor

Model: IND30 Single Indoor

- Size: 8 in x 8 in x 6 in
- Lift - Off cover
- Environmental Rating: NEMA 1
- Material: Powder Coated Steel
- Color: Gray
- Knockouts: 16
- Mounting Holes: 4
- Empty Enclosure Certifications:
UL Listed and CSA Certified



- Maximum (Max) Line Voltage: 250 VAC, RMS, 50/60 Hz.
- Nameplate Max Current all IND30 models: 30 amperes AC, RMS, 50/60 Hz.
- For Filtering Performance, Max Current all IND30 models: 35 amperes AC, RMS, 50/60 Hz.
- For Safety/Overload Max Current all IND30 models: 42 amperes AC, RMS, 50/60 Hz.
- Max. Wire gauge on internal terminal strip IND30: 4 AWG (accepts 18 AWG to 4 AWG)
- Current Capacity of Internal Wiring: 55 amps RMS
- Current Capacity of Terminal Strip: 85 amps RMS
- Assembled Weight: 19 lbs.
- Note: There are various loads that can cause the IND to audibly buzz. This is normal operation.
- **Enclosure and All components inside enclosure are UL Listed.**

Noble Electronics, Inc.

1973 155th St. Fairfield, IA 52556, <http://mxdna.com>

We have 23 Dealers throughout the US. Visit our website to find a Dealer close to you.